


WAAS CH 69202 W05A	APP CRS 053°	Rwy Idg 9004 TDZE 931 Apt Elev 958
--	------------------------	---

RNAV (GPS) RWY 5
DES MOINES INTL (DSM)

RNP APCH - GPS. ⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500. *RVR 1800 authorized with use of FD or AP or HUD to DA (NA when using Ankeny Rgnl altimeter setting).	MALSR 	MISSED APPROACH: Climb to 3100 direct IOWAA and hold.
---	-----------	---

ATIS 119.55	DES MOINES APP CON 123.9 307.15	DES MOINES TOWER 118.3 257.8	GND CON 121.9 348.6	CLNC DEL 134.15 317.55
-----------------------	---	--	-------------------------------	----------------------------------



ELEV 958 D TDZE 931				
REIL Rwy 5 and 23 TDZ/CL Rwy 31 HIRL Rwy 13-31 and 5-23				
DES MOINES, IOWA Amdt 4 30NOV23				

CATEGORY	A	B	C	D
LPV DA *	1131/24		200 (200-½)	
LNAV/VNAV DA	1247/24		316 (300-½)	
LNAV MDA	1320/24	389 (400-½)	1320/35	389 (400-¾)
C CIRCLING	1420-1	462 (500-1)	1600-1¾ 642 (700-1¾)	1760-2½ 802 (900-2½)

