

WAAS CH 70435 W22A	APP CRS 222°	Rwy Idg 6900 TDZE 152 Apt Elev 158
--	------------------------	---


RNAV (GPS) RWY 22

ROCKY MOUNT/WILSON RGNL (RWI)


V For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -10°C (14°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Wayne Exec Jetport altimeter setting. When local altimeter setting not received, use Wayne Exec Jetport altimeter setting and increase all DA 59 feet and all visibilities ¼ mile; increase all MDA 60 feet and LNAV Cats C/D and Circling Cat C visibility ¼ mile. Rwy 22 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:
Climb to 1000 then
climbing right turn to
2500 direct FENIM
and hold.

ASOS 118.875	WASHINGTON CENTER 123.85 279.65	UNICOM 123.05 (CTAF) 0
------------------------	---	----------------------------------



ELEV	158		TDZE	152
------	-----	---	------	-----



REIL Rwy 22 **L**
HIRL Rwy 4-22 **L**

1000 2500 FENIM

VGS1 and RNAV glidepath not coincident (VGS1 Angle 3.00/TCH 42)

4 NM Holding Pattern

*LNAV only.

BUDAY 2.4 NM to RW22

BONAC 1800

FENIM

042° → 2500

← 222°

222°

1800

960*

*1.2 NM to RW22

RW22

GP 3.00° TCH 52

1.2 1.2 NM 2.6 NM 6.8 NM

CATEGORY	A	B	C	D
LPV DA		436-7/8 284 (300-7/8)		
LNAV/VNAV DA		513-1 3/8 361 (400-1 1/8)		
LNAV MDA	560-1 408 (500-1)		560-1 1/8 408 (500-1 1/8)	
CIRCLING	600-1 442 (500-1)	620-1 462 (500-1)	720-1 1/2 562 (600-1 1/2)	760-2 602 (700-2)

RNAV (GPS) RWY 22